

**DESCRIPTION**

**MODEL: LS-VS-01C-2**

**CONTACT CAPACITY: AC220V/1A;DC24V/0.5A**

**WORKING PRESSURE: ATM**

**OUTPUT SIGNAL: SPST NO/NC.**

**TEMP RATING-. 20-100°C, 150°C, 200°C**

**MATERIAL: SUS 304 (SUS316 OPTIONAL)**

**PROTECTION GRADE:IP68**

**FLOATSIZE: 28²28MM**

**CONNECTION: M10;G1/8", NPT ½"(CUSTOMIZED)**

**INSERT LENGTH: 100MM, 150MM,200MM**



## Descripción

OUTPUT SIGNAL: SPST NO/NC.  
TEMP RATING-. 20-100°C, 150°C, 200°C

MATERIAL: SUS 304 (SUS316 OPTIONAL)  
PROTECTION GRADE:IP68  
FLOATSIZE: 28<sup>ø</sup>28MM  
CONNECTION: M10;G1/8", NPT 1/2"(CUSTOMIZED)  
INSERT LENGTH: 100MM, 150MM,200MM

WEZZ USA  
4224 China Road Blvd  
St. Albans, N. York 12057  
Newark, NJ 07102

(304) 348-2388  
FAX (304) 348-6271  
info@wezz.com

